

PTFE ADDITIVE TA - 105

SERIE
100

Product description

MOTON TA 105 is an oil additive based on a high-quality pure mineral oil. This guarantees an excellent miscibility and compatibility with all usual oils for industrial applications, except for rape seed oil. PTFE has an extremely low coefficient of friction and is completely inert. It reduces damage caused by metal to metal contact as a result of a broken lubrication film on your application. As a result, it reduces wear, pitting and stick-slip.

Application area

To add to all motor case lubrication systems as a lubricant of:

- gear boxes
- differentials
- hydraulic oil systems
- engines

Applicable to:

- industry
- transport
- offshore etc.

Delivery

5 litre (TA-105-005), 10 litre (TA-105-010) cans
60 litre (TA-105-060), 200 litre (TA-105-200) drums.

Features



Addition >2%. When oil agitates premixing is not necessary, To obtain an optimal result premix in case of slow flowing systems

Advantages

In engines:

- ✓ Reduction of friction and wear
- ✓ Improvement of engine elasticity
- ✓ Improvement of cold start
- ✓ Reduction of "Blow-By"
- ✓ Reduction of gas- and oilconsumption

In gearboxes:

- ✓ Reduction of friction and wear
- ✓ Reduction of pitting, especially in combination with HD-oils
- ✓ Lower starting torque
- ✓ levels top loads

In hydraulic systems:

- ✓ Eliminates Stick-Slip
- ✓ Improves regulation system
- ✓ Lower starting torque of hydromotors
- ✓ Less energy consumption

color	white
components	mineral oil, additives, PTFE
density	ca. 0,95
viscosity	liquid
filter safe	>25 micron